



POWER MAX

SAE 20W50 - API: SL/CF; ACEA: A3B4

GASOLENE ENGINE OIL

DESCRIPTION

U-Lube Power Max is new generation of automotive oils based on revolutionary concepts meeting the performance level required by today's gasoline engines. Blended with premium quality additives to give exceptional performance in most severe operating conditions. It provides excellent resistance to Oxidation wear and corrosion.

APPLICATION

- U-Lube Power Max is recommended for gasoline and most diesel engine passenger and commercial vehicles of naturally aspirated or turbo charged engines which requires API SL/CF and earlier categories.
- It meet the performance requirements of most European, Japanese and American Passenger Car Manufacturers.

BENEFITS

- Superior anti-wear and anti-scutting properties.
- Excellent corrosion protection of engine parts.
- Stable under heavy load and higher temperatures.
- Good to operate in all four seasons of the year.

SPECIFICATIONS

API: SL/CF; ACEA: A3B4

TYPICAL PROPERTIES

Properties	Results	Method
SAE Viscosity Grade	20W50	-----
Density @ 15° C, g/ml	0.886	ASTM D-1298
Flash Point, COC, °C	230	ASTM D-92
Pour Point, °C	-24	ASTM D-97
TBN, mgKOH/g	8	ASTM D-2896
Viscosity @ 100°C, cSt	17.5	ASTM D-445
Viscosity Index	130	ASTM D-2270

