



# POWER MAX (FULL SYNTHETIC)

SAE 5W30 - API SL/CF: ACEA A3/B4

## GASOLINE ENGINE OIL

### DESCRIPTION

U-LUBE POWER MAX is formulated with fully synthetic oil based with highly advance additives package having low sulfur, phosphorous and less ash content. The high technology additive provides good thermal stability, oxidation resistance & high power in engine.

### APPLICATION

U-LUBE POWER MAX 5W30 fully synthetic motor oil is recommended for all types of modern vehicles, including high Performance with or without turbo charged, super charged gasoline and diesel multi valve fuel injected engines found in passenger cars, SUVs, light vans and trucks.

### BENEFITS

- Outstanding protection against rust, wear and sludge formation.
- Good thermal stability and oxidation resistance.
- Faster circulation in engine, giving good startup performance.
- Maintain engine cleanliness.
- Superior protection of exhaust emission control system.
- Outstanding low temperature fluidity.
- Immediate lubrication in cold condition during engine startup.

### SPECIFICATION

API : SL/CF, MB 229.3, VW 502.00/505.00

### PRODUCT CHARACTERISTICS:

| Test Parameter    | Units              | Typical Results | Method       |
|-------------------|--------------------|-----------------|--------------|
| Appearance        | ---                | C&B             | Visual       |
| Density @ 15°C    | g/ml               | 0.865           | ASTM D-1298  |
| Viscosity @ 40°C  | mm <sup>2</sup> /s | 60              | ASTM D-7042  |
| Viscosity @ 100°C | mm <sup>2</sup> /s | 10.5            | ASTM D-7042  |
| Viscosity Index   | ---                | 167             | ASTM D- 2270 |
| Flash Point (COC) | °C                 | 220             | ASTM D-92    |
| Pour Point        | °C                 | -39             | ASTM D-97    |
| Base Number       | mg of KOH/gr       | 8               | ASTM D-2896  |

