

## TECHNICAL SPECIFICATION

**Product Name: SOLVENT HEAVY EXTRACT**

| #  | PARAMETERS                   | ASTM D | UNIT     | SPECS.        |
|----|------------------------------|--------|----------|---------------|
| 1  | Appearance                   | Visual | -        | DARK BROWN    |
| 2  | Density @ 15°C               | 7042   | g/mL     | 0.885 – 0.940 |
| 3  | Kinematic Viscosity @ 40 °C  | 445    | cSt      | 35 - 65       |
| 4  | Kinematic Viscosity @ 100 °C | 445    | cSt      | 5.0 – 7.0     |
| 5  | Viscosity Index, Min.        | 2270   | -        | 40            |
| 6  | Flash Point, COC, Min.       | 92     | °C       | 190           |
| 7  | Flash Point, PMCC, Min.      | 93     | °C       | 170           |
| 8  | Neutralization No. , Max.    | 974    | mg KOH/g | 0.1           |
| 9  | Sulphur Content, Max.        | 4294   | Wt. %    | 1.0           |
| 10 | Ash Content, Max.            | 482    | Wt., %   | 0.6           |

Issue Date: December, 2017

Doc #: FM:TS:57

Revision: 1

Page #: 1 of 1

