



## GAMMA (I)

EP GEAR OIL - ISO 150; 220; 320

# INDUSTRIAL OILS

### DESCRIPTION

U-Lube Gamma Extreme Pressure Gear oil is excellent quality gear Lubricants specially formulated with world class additives to provide high load carrying capacity, intended for Gear boxes, Spiral Bevel Axles, operating under severe conditions of high speed/shock load service.

### APPLICATION

- Industrial gear units requiring an extreme pressure type of oil.
- Industrial equipment such as helica, bevel, spur and planetary gears.
- Automotive & Manual transmission of heavy equipment, trucks & buses.

### BENEFITS

- High thermal and Oxidation stability.
- Excellent load-carrying capacity.
- Excellent anti-wear; Rust and Corrosion resistance.
- Good Seal Compatibility.
- Improved lubrication of gear box bearings.

### SPECIFICATIONS

AGMA 9005 -EO2; DIN51517 Part 3; ISO 12925 - CKC/CKD

### TYPICAL PROPERTIES

SAE Grade	150	220	320	Test Method
Density @ 15° C, g/ml	0.895	0.898	0.902	ASTM D-1298
Viscosity @ 40°C, cSt	150	220	320	ASTM D-445
Viscosity @ 100°C, cSt	14.8	19.2	24.3	ASTM D-445
Viscosity Index	98	98	97	ASTM D-2270
Flash Point, COC, °C	250	254	258	ASTM D-92
Pour Point, °C	-15	-15	-15	ASTM D-97

