



TURBO

SAE 40, 50 - API : CF; ACEA:E2

DIESEL ENGINE OIL

DESCRIPTION

It is designed for heavy duty on-road and off-road turbo charged or naturally aspirated diesel engines operating under high load conditions. Formulated with selected base oils and Superior Quality additives which requires excellent detergent, dispersant, good oxidation stability and maintain good anti-wear and anti-corrosion for engine.

APPLICATION

- It is recommended for use in turbo charged and naturally aspirated diesel engine for heavy duty Trucks, commercial Vehicles, Passenger cars and Pickups.
- And also recommended for use in agricultural and construction equipments, operating in fleet and construction business.

BENEFITS

- Sludge free oil environment in engines.
- Provides uniform oil layer at the sides of engines.
- High quality detergent and dispersant oils bringing economy and quality together
- Good Anti-wear Properties

SPECIFICATIONS

API: CF/SF; ACEA:E2

TYPICAL PROPERTIES

Properties	Results		Method
SAE Viscosity Grade	50	40	
Density @ 15° C, g/ml	0.895	0.888	ASTM D-1298
Flash Point, COC, °C	240	240	ASTM D-92
Pour Point, °C	-12	-18	ASTM D-97
TBN mg KOH/g	11	11	ASTM D-2896
Viscosity @ 100°C, cSt	18	14.5	ASTM D-445
Viscosity Index	99	99	ASTM D-2270

