



HEAVY DUTY BRAKE FLUID

DOT 3

SPECIALITY PRODUCTS

DESCRIPTION

U-Lube Heavy Duty Brake Fluid is formulated with high quality non petroleum chemical fluid. It provides maximum wet boiling point protection against vapour lock brake failure. This fluid is working under extreme desert heat, arctic cold for corrosion control.

APPLICATION

Recommended for all anti-lock braking systems (ABS), hydraulic drum and disc braking systems and hydraulic clutches requiring DOT 3.

BENEFITS

- All season Protection.
- Protects against metal corrosion.
- Compatible with rubber components.
- Prevents seal hardening or softening.
- Mixes with conventional brake fluids.

SPECIFICATIONS

SAE J1703, J1704 FMVSS No. 116 DOT 3 and DOT 4 MOTOR VEHICLE BRAKE FLUID

TYPICAL PROPERTIES

Properties	Results DOT 3	Method
Equilibrium Reflux Boiling Point, °C	240	FMVSS116
Wet E. R. Boiling Point, °C	145	FMVSS116
Viscosity @ 100°C, cSt	2.1	ASTM D-445
pH	8.6	FMVSS116
Specific Gravity, 15°C	1.18	ASTM D-1298
Flash Point, COC, °C	150	ASTM D-92

