



TURBO PLUS

SAE 15W40 - API: CF/CF4; ACEA: B3E2

DIESEL ENGINE OIL

DESCRIPTION

It is formulated with selected high quality refined mineral base oils and enriched with advanced technology additives to provide optimum control over deposits in severe service and control against wear, rust and corrosion. Meets and exceeds API's CF for on-road and off-road applications.

APPLICATION

- Four season multi grade diesel engine oil is specially developed for high output trucks, buses, passenger cars and vans.
- Recommended for use in agricultural and construction equipments where it requires.

BENEFITS

- Excellent starting in all four seasons of the year.
- Provides good Oxidation stability.
- Splendid detergents keep the engine parts clean.
- Sludge free oil environment in engine.

SPECIFICATIONS

API: CF/CF4; ACEA: B3E2; MB 228.0

TYPICAL PROPERTIES

Properties	Results	Method
SAE Viscosity Grade	15W40	-----
Appearance	Clear	Visual
Density @ 15° C, g/ml	0.884	ASTM D-1298
Flash Point, COC, °C	220	ASTM D-92
Pour Point, °C	-30	ASTM D-97
TBN, mg KOH/g	10	ASTM D-2896
Viscosity @ 100°C, cSt	13.5	ASTM D-445
Viscosity Index	135	ASTM D-2270

