



POWER
SAE 40 - API : SG

GASOLENE ENGINE OIL

DESCRIPTION

U Lube Power is premium quality engine oil formulated with selected base oil and highest quality performance additives which provides good Oxidation Stability, dispersant & detergent characteristics to meet API SG level .It is high quality mono grade gasoline engine oil for turbocharged or normally aspirated gasoline engines, working under severe conditions.

APPLICATION

- U Lube Power is recommended for naturally aspirated or turbocharged engines in light vehicles, Passenger cars & Commercial vehicles.
- This oil may also be used in general lubrication of various equipments.

BENEFITS

- Controls the corrosive effect of combustion products.
- Stable under heavy load and higher temperature.
- Effective lubrication film on the sides of the engines.
- Does not form foam and oil loss is minimum.

SPECIFICATIONS

API: SG

TYPICAL PROPERTIES

Properties	Results	Method
SAE Viscosity Grade	40	-----
Density @ 15° C, g/ml	0.888	ASTM D-1298
Flash Point, COC, °C	240	ASTM D-92
Pour Point, °C	-21	ASTM D-97
TBN mg KOH/g	7	ASTM D-2896
Viscosity @ 100°C, cSt	13	ASTM D-445
Viscosity Index	96	ASTM D-2270

